

1. 我國已宣布 2050 要達成淨零排放目標。請問政府可以設計哪方面的誘因機制規劃，減少建築排放，請說明(25%)
2. 我國處於高地震帶區域，且都市居住密集度高，未來高層建築設計需求增加。請問在考量成本的情況下，哪種建築結構類型可減少排放量。政府可以做哪些配套規劃(如法規、誘因機制設計)，請說明(30%)
3. 考量我國本土成本與資源有限情況，請提出適用於地震帶區域的低碳建築設計策略，以平衡環境永續性與抗震需求(25%)
4. 離岸風力為我國未來發展低碳發電之主要來源。請說明發展離岸風電國產化是否會造成什麼問題或帶來什麼效益，使得現在經濟部放棄國產化規範。請說明(20%)

1. Please define the terminologies of (a) Spectroscopy (b) Mass-spectroscopy and (c) Diffraction techniques. (10)
2. Fourier Transform Infrared Spectroscopy (FTIR) is commonly used to analyze organic materials. (a) Explain the role of "Fourier Transform" in this technique and how it is applied to convert the raw data into a usable spectrum. (b) Describe how to interpret the data obtained from FTIR, focusing on identifying functional groups and understanding the significance of the absorption peaks in the spectrum. (10)
3. Explain the working principle of Raman spectroscopy and how it differs from infrared (IR) spectroscopy in terms of vibrational mode selection (Raman-active vs. IR-active). Discuss the key differences between Raman and fluorescence signals, including their excitation mechanisms and spectral characteristics. If fluorescence occurs during Raman measurements, what strategies can be used to minimize or avoid it in order to obtain clear Raman spectra?
4. How does preferred orientation affect an X-ray diffraction (XRD) pattern in terms of peak intensities and missing reflections? Explain how the pattern may differ from a randomly oriented sample and why these changes occur. Finally, discuss experimental techniques to minimize the effects of preferred orientation. (15)
5. XRD peak broadening may be created by the size or strain effect. Please describe how "size" and "strain" effect generate to the full-width-half-maximum (FWHM) as a function of the incident angle of light. (5)
6. X-ray Photoelectron Spectroscopy (XPS) is a surface-sensitive technique used to analyze the elemental composition and chemical state of materials. (a) Explain the working principle of XPS, including how it detects elements and provides information on their chemical states. (b) What kind of information can be obtained from an XPS spectrum, and how can the binding energy shifts be used to interpret the chemical environment of elements in the sample? (15)
7. X-ray Fluorescence (XRF) and Energy Dispersive X-ray Spectroscopy (EDXS) are two techniques used for elemental analysis of materials. (a) Compare the working principles of XRF and EDXS, focusing on how each technique detects elements in a sample. (b) Highlight the differences in the type of data obtained from XRF and EDXS, and how the

results can vary in terms of resolution and sensitivity. (10)

8. Scanning Electron Microscopy (SEM) and Transmission Electron Microscopy (TEM) are two imaging techniques used to analyze materials at the nanoscale. (a) Compare the working principles of SEM and TEM, focusing on how each technique forms an image. (b) Discuss the differences in sample preparation for SEM and TEM, including the requirements for sample thickness, conductivity, and any coating or treatment needed before analysis. (15)
9. Atomic Absorption Spectroscopy (AAS) and Inductively Coupled Plasma Spectroscopy (ICP) are commonly used techniques for measuring the concentration of elements in a solution. (a) Explain the working principles of AAS and ICP. (b) Compare the differences in the type of data obtained from these two methods, including sensitivity, detection limits, and the range of elements that can be analyzed. (10)

吳鎮坤